

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International BureauP350548
FM CASE 3028


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16D 55/40, 65/12	A1	(11) International Publication Number: WO 00/09903 (43) International Publication Date: 24 February 2000 (24.02.00)
(21) International Application Number: PCT/GB99/02415 (22) International Filing Date: 26 July 1999 (26.07.99) (30) Priority Data: 9817759.5 15 August 1998 (15.08.98) GB	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(71) Applicant (for all designated States except US): FEDERAL-MOGUL TECHNOLOGY LIMITED [GB/GB]; Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): BUNKER, Kenneth, James [GB/GB]; 39A Mill Road, Rearsby, Leicester LE7 4YN (GB). (74) Agent: DRURY, Peter, Lawrence; T & N Limited, Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB).	Published <i>With international search report.</i>	

(54) Title: MULTIPLE DISC BRAKE SYSTEM

(57) Abstract

A disc brake system (10) comprises a disc (12, 14), and a hub (16) which is arranged to rotate about an axis (18) thereof. The system (10) also comprises mounting means (20, 22) by which the disc (12, 14) is mounted on the hub (16) so that the hub and the disc rotate as a unit about said axis (18) and the disc can perform axial sliding movement on said hub. Said mounting means comprises a plurality of axially-extending grooves (20) formed in the hub (16) and teeth (22) projecting from the disc (12, 14) into said grooves. The system (10) also comprises resilient means (32; 42) acting to apply radial force between the disc (12, 14) and the hub (16). Said resilient means is provided by spring (32; 42) located in at least some of said grooves (20) and engaging the teeth (22).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MULTIPLE DISC BRAKE SYSTEM

This invention is concerned with a disc brake system,
~~for example for a wheel of a vehicle.~~

A conventional disc brake system comprises a hub mounted on a suspension link for rotation relative thereto, the hub providing a mounting for a wheel, and a disc brake comprising a disc mounted for rotation as a unit with the hub, friction material pads arranged on opposite sides of the disc, and at least one piston and cylinder assembly operable to urge the pads into engagement with the disc, to brake the hub and hence the wheel. Conventionally, the piston and cylinder assembly is slidably mounted on a slide bolted to the suspension link of the vehicle. The disc is conventionally rigidly fixed to the hub, and wear of the pads and/or the disc is accommodated by the sliding movement of the cylinder.

Disc brake systems are known in which the disc rotates with the hub as a unit but can perform sliding movement on the hub. For example, see GB 1 396 503 and WO 98/25804. However, since the discs are relatively thin, they tend to tilt on the hub and affect the braking ability. Also, there is a tendency for noise to be produced by rattle of the disc against the hub. At higher disc temperatures, these problems can be particularly severe since, when there is a large temperature differential, such as 600°C, between the braking surface of the disc and the hub, the disc expands considerably, away from the hub, exacerbating the problems of tilting and rattle. These problems are addressed in WO 98/26192 in which the solution proposed is to provide a plurality of resilient force applicators which

are mounted between the hub and the disc, the force applicators acting to apply radially-directed forces to the disc to control the movement thereof, the force applicators being distributed circumferentially around the hub. In the example given in WO 98/26192, the disc brake system comprises two discs mounted on the same hub. One mounting means for the disc on the hub disclosed in WO 98/26192 ~~comprises groups of axially-extending grooves formed in the~~ hub and teeth projecting from the discs into said grooves, the teeth being slidable along the grooves. The force applicators are in the form of leaf springs mounted on the hub in the spaces between the groups of grooves. This system requires that, at least between the groups of grooves, there is sufficient clearance between the hub and the discs to accommodate the leaf springs and flexing thereof. This clearance has the disadvantage that it increases the possibility that a disc may tilt relative to the hub, thereby adversely affecting the operation of the brake.

It is an object of the present invention to provide a disc brake system in which the afore-mentioned disadvantage is overcome or at least reduced.

The invention provides a disc brake system comprising a disc, and a hub which is arranged to rotate about an axis thereof, the system also comprising mounting means by which the disc is mounted on the hub so that the hub and the disc rotate as a unit about said axis and the disc can perform axial sliding movement on said hub, said mounting means comprising a plurality of axially-extending grooves formed in the hub and teeth projecting from the disc into said grooves, each tooth being a sliding fit in one of said grooves, the system also comprising resilient means acting to apply radial force between the disc and the hub, characterised in that said resilient means is provided by springs located in at least some of said grooves and

engaging the teeth of the disc which project into those grooves to apply radial force to said teeth.

In a disc brake system according to the invention, the springs are accommodated in the grooves in the hub so that space for them does not have to be provided between the grooves enabling the clearance to be reduced substantially. ~~This enables the possibility of the disc tilting on the hub~~ to be reduced.

A disc brake system according to the invention may be as disclosed in WO 98/25804, except that the splined mounting means by which discs are mounted on a hub is replaced by mounting means as disclosed herein. The brake system of WO 98/25804 comprises one or more discs which are slidable on a hub under the control of leaf springs which act between the hub and the discs. The system also comprises a cylinder which is integrally formed with a suspension link and a caliper also fixed to the suspension link, the caliper having supports for friction material pads mounted thereon.

In a disc brake system according to the invention, the springs may be flat leaf springs as disclosed in WO 98/26192 or any other suitable type of spring. For example, the springs may be leaf springs each of which comprises at least three abutments which project transversely of the spring and engage the disc so that the abutments apply force to the disc. This arrangement has the advantage that the number of points of contact between the spring and the disc is increased thereby spreading the forces more evenly around the disc. The abutments may be provided by embossed portions of the spring. The abutments, preferably, are elongated so that each abutment remains in engagement with the disc throughout said movement of the disc on the hub. For example, said abutments may be in the form of ridges extending parallel

to the axis about which the hub rotates. The leaf springs may be secured to the outer surface of the hub in a manner such that the springs extend tangentially of the hub when the disc is not mounted on the hub. Cut-outs, eg holes, may be formed in the leaf springs to control the force applied by the abutments to the disc. Where the disc brake system comprises one or more further discs mounted on the hub, ~~the leaf springs may be arranged in groups, one spring~~ in each group being associated with each disc, at least one spring in each group being retained in position by a connection to another spring in said group.

There now follows a detailed description, to be read with reference to the accompanying drawings, of a disc brake system which is illustrative of the invention.

In the drawings:

Figure 1 is an end view of the illustrative disc brake system;

Figure 2 is a cross-sectional view, on a larger scale, taken on the broken line II-II in Figure 1;

Figure 3 is a perspective view, on a greatly enlarged scale, of a leaf spring of the illustrative disc brake system; and

Figure 4 is a view similar to Figure 3 but of an alternative leaf spring of the illustrative disc brake system.

The illustrative disc brake system 10 shown in Figures 1 and 2 is for a wheel (not shown) of a car. The system 10 comprises a disc 12, a further disc 14 and a hub 16, on which the wheel can be mounted. The hub 16 is arranged to rotate about a central axis 18 thereof.

The hub 16 comprises an internally splined hollow inner cylindrical portion 16a which is arranged to receive a drive shaft (not shown) which drives the wheel. The hub

16 also comprises an external flange 16b at one end of the portion 16a. This flange 16b has four bolt holes 16c through which the wheel can be bolted to the flange 16b in a conventional manner. The flange 16b also serves to connect the portion 16a to an outer hollow cylindrical portion 16d of the hub 16.

The discs 12 and 14 are identical to one another, being in the form of generally-annular cast iron or steel plates. The two discs 12 and 14 are mounted by means of mounting means of the system 10 on the cylindrical outer surface of the hub portion 16d so that the hub 16 and the two discs 12 and 14 rotate as a unit about the axis 18 and the discs 12 and 14 can perform axial sliding movement on said hub 16. The mounting means comprises four grooves 20 which are formed in the outer cylindrical surface of the portion 16d of the hub 16 and four teeth 22 which project inwardly from each of the discs 12 and 14. The teeth 22 enter the grooves 20 and are a sliding fit therein. However, the teeth 22 do not extend to the bottom surfaces 20a of the grooves 20, there being a clearance between the bottom surfaces 20a and the inner surfaces 22a of the teeth 22. The grooves 20 are equally-spaced circumferentially about the axis 18 and each occupies an arc of approximately 45° about the axis 18. Between the grooves 20, the outer surface of the hub portion 16d is machined to be accurately cylindrical about the axis 18. The inner surface of each disc 12 and 14, between the teeth 22, is also machined to be accurately cylindrical about the axis 18 and a close fit over the cylindrical portions of the outer surface of the hub portion 16d. The close fit of the discs 12 and 14 on the hub 16 reduces the possibility of the discs 12 and 14 tipping.

The system 10 also comprises four friction pads 26 (Figure 2) for braking the discs 12 and 14 by engaging side surfaces of the discs. The friction material pads 26 are

secured to three backing plates 28, one backing plate 28a being between the discs 12 and 14 and the others being on opposite sides of the discs 12 and 14 to the plate 28a. The median plate 28a has friction pads 26 secured to both of its faces. The brake pads 26 and the backing plates 28 are not shown in Figure 1. The brake pads 26 are brought into braking contact with the discs 12 and 14 by operating means ~~(not shown) which may be similar to that described in~~ WO 98/25804. When the brakes are applied, a movable outer friction material pad 26 is moved until the four pads 26 and the discs 12 and 14 are all in contact with one another, the discs 12 and 14 and the plate 28a sliding axially to accommodate this movement.

The system 10 also comprises resilient means acting to apply radial force between the discs, 12 and 14, and the hub 16. The resilient means comprises four leaf springs 32 mounted on the hub 16 and engaging the discs 12 and 14 so that the springs 32 apply radial force between each of the discs 12 and 14 and the hub 16. The leaf springs 32 are equally distributed circumferentially around the hub 16, each being mounted on one of the bottom surfaces 20a of the grooves 20, ie the springs 32 are located in the grooves and act between the surface 20a and the inner surface 22a of the tooth 22 which enters the groove 20.

One of the leaf springs 32 is shown in detail in Figure 3. Each spring 32 is formed from a generally rectangular piece of spring steel which is 0.25 - 0.3mm thick. Each spring 32 is secured in the circumferential centre of one of the surfaces 20a by means of a central screw 36 which passes through a hole 32a in the spring 32 and enters the hub 16. Each spring 32 extends axially on the hub 16 throughout the range of axial movement of both discs 12 and 14 so that both discs 12 and 14 are engaged by all four of the springs 32 continuously. The springs 32 act to control the sliding movement of the discs 12 and 14

on the hub 16 preventing tipping of the discs and compensating for thermal expansion effects.

Each spring 32 comprises four axially-extending abutments 40 which project transversely of the spring 32. The abutments 40 are arranged with two of the abutments on each side of the hole 32a. Two of the abutments 40 are formed at the extreme ends of the spring 32, thereby preventing the edge of the spring 32 from engaging the tooth 22 and reducing the risk of cracking of the spring 32. Between the two abutments 40 on each side of the hole 32a, a rectangular hole 32b is cut out of the spring 32. The hole 32b serves to control the force applied by the abutments 40 to the discs 12 and 14.

The abutments 40 are provided by embossed portions of the spring 32 which are in the form of generally semi-circular (in transverse cross-section) ridges extending parallel to the axis 18. The abutments 40 are elongated in the axial direction so that each abutment 40 remains in engagement with both of the discs 12 and 14 throughout the movement of the discs 12 and 14 on the hub 16.

Each spring 32 is arranged to engage the discs 12 and 14 with its abutments 40 and apply force to the discs to control the movement thereof on the hub 16. Each spring 32 is arranged so that the spring 32 extends generally tangentially of the hub 16 when the discs 12 and 14 are not mounted on the hub 16. However, the springs 32 are deformed by the presence of the discs 12 and 14 so that each abutment 40 presses resiliently on the discs 12 and 14. The springs 32, thus, act to apply radially-directed forces to the discs 12 and 14.

In the operation of the disc brake system 10, the springs 32 as aforementioned control the sliding movement of the discs 12 and 14 on the hub 16. Each spring 32

engages each disc at four points of contact, provided by the abutments 40, thereby distributing the force applied by the spring 32 to each disc more uniformly.

Figure 4 shows two leaf springs 42 which are joined together by a narrow tab 44, the springs 42 and the tab 44 being formed from a single sheet of spring steel. The two leaf springs 42 each have a similar form to the spring 32 except that the holes 32b are omitted, each spring 42 having four abutments 46 which are similar to the abutments 40 of the spring 42. However, the springs 42 are narrower than the spring 32 because each spring 42 is intended to engage only one of the discs 12 and 14. The springs 42 are mounted on the surfaces 20a (as a unit connected by the tab 44) by means of a screw (not shown) which passes through a hole 42a formed in one of the springs 42. Thus, each of the discs 12 and 14 has four of the leaf springs 42 associated therewith, the springs 42 being arranged in groups of two, one of which is mounted on the hub 16 and the other of which is retained in position by the connection, via the tab 44, to the first-mentioned spring. As the tab 44 is narrow, the springs 42 act substantially independently.

In modifications of the springs 32 and 42, the holes 32a and 42a may be omitted and the springs provided instead with self-retaining means for retaining them on the hub 16. For example, such self-retaining means may comprise integral tabs extending from the spring over opposite ends of the hub 16 so that the springs can be clipped over the hub. In the case of the spring 32, such tabs extend normally to the general plane of the spring from both the edges of the spring which are perpendicular to the projections 40. In the case of the springs 42, each of the end springs 42 in a group has one of these tabs extending from its opposite edge to the position of the tab 44.


In a further modification, the springs 32 and 42 can be formed into a non-planar form in order to determine the forces they will apply to the disc. For example, the springs can be formed into an arcuate shape such that, when the spring is mounted on the hub but before the discs are mounted on the hub, the ends of the spring are further from the hub than if the spring were planar.

CLAIMS


- 1 A disc brake system (10) comprising a disc (12), and a hub (16) which is arranged to rotate about an axis (18) thereof, the system also comprising mounting means (20, 22) by which the disc is mounted on the hub so that the hub and the disc rotate as a unit about said axis and the disc can perform axial sliding movement on said hub, said mounting means comprising a plurality of axially-extending grooves (20) formed in the hub (16) and teeth (22) projecting from the disc (12) into said grooves, each tooth (22) being a sliding fit in one of said grooves (20), the system (10) also comprising resilient means (32; 42) acting to apply radial force between the disc (12) and the hub (16), characterised in that said resilient means is provided by springs (32; 42) located in at least some of said grooves (20) and engaging the teeth (22) of the disc (12) which project into those grooves (20) to apply radial force to said teeth (22).
- 2 A disc brake system according to claim 1, characterised in that said springs (32; 42) are leaf springs.
- 3 A disc brake system according to claim 2, characterised in that each of said leaf springs (32; 42) comprises at least three abutments (40; 46) arranged to engage the tooth (22) and apply force thereto.
- 4 A disc brake system according to claim 3, characterised in that said abutments (40; 46) are provided by embossed portions of the spring (32; 42).

- 5 A disc brake system according to either one of claims 3 and 4, characterised in that said abutments (40; 46) are elongated so that each abutment remains in engagement with the disc (12) throughout said movement of the disc on the hub (16).
- 6 A disc brake system according to any one of claims 3 to 5, characterised in that said abutments (40; 46) are in the form of ridges extending parallel to the axis (18) about which the hub (16) rotates.
- 7 A disc brake system according to any one of claims 2 to 6, characterised in that the leaf springs (32; 42) are secured to the outer surface of the hub (16) in a manner such that the springs extend tangentially of the hub when the disc (12) is not mounted on the hub.
- 8 A disc brake system according to any one of claims 2 to 7, characterised in that cut-outs (32b) are formed in the leaf springs (32) to control the force applied by the abutments (40) to the disc (12).
- 9 A disc brake system according to any one of claims 2 to 8, characterised in that the system (10) comprises one or more further discs (14) mounted on the hub (16), and in that the leaf springs (42) are arranged in groups, one spring (42) in each group being associated with each disc (12, 14), at least one spring in each group being retained in position by a connection (44) to another spring in said group.
- 10 A disc brake system according to any one of claims 2 to 9, characterised in that the leaf springs (32; 42) are provided with self-retaining means for retaining them on the hub (16).


1/4

*Fig. 1*

2/4

*Fig. 2*

3/4

*Fig. 3*

4/4




Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/02415

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16D55/40 F16D65/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 98 26192 A (BUNKER KENNETH JAMES ; T & N TECHNOLOGY LTD (GB)) 18 June 1998 (1998-06-18) cited in the application	1-4
A	page 4, last paragraph -page 6, paragraph 2; figures 1,2	8
Y	US 5 674 026 A (ISHIBASHI TOSHIO ET AL) 7 October 1997 (1997-10-07)	1-4
A	column 3, line 29 -column 4, line 21; figures 2,17,18	5,10
A	US 4 534 457 A (ELTZE GEORG ET AL) 13 August 1985 (1985-08-13) the whole document	1,2,4,7, 9,10
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

18 October 1999

Date of mailing of the international search report

26/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gertig, I

PCT/GB 99/02415

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/02415

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9826192 A	18-06-1998	AU 5404498 A EP 0944780 A GB 2320299 A	03-07-1998 29-09-1999 17-06-1998
US 5674026 A	07-10-1997	JP 8049726 A CN 1120636 A DE 19506517 A US 5645366 A	20-02-1996 17-04-1996 31-08-1996 08-07-1997
US 4534457 A	13-08-1985	DE 3302430 C FR 2539831 A GB 2134606 A, B JP 1776281 C JP 4061209 B JP 59137621 A	22-03-1984 27-07-1984 15-08-1984 28-07-1993 30-09-1992 07-08-1984
DE 2039003 A	18-02-1971	ES 382476 A FR 2056625 A JP 50030789 B ZA 7005340 A	01-12-1972 14-05-1971 03-10-1975 28-04-1971